

Permit No. _____
Owner: _____
Site Address: _____
Contractor: _____



MOISTURE CONTENT ACKNOWLEDGEMENT

To conform with Section R318 of the 2021 Oregon Residential Specialty Code (ORSC), I am notifying the building official that I am aware of the moisture content requirement and have taken steps to meet this code requirement.

SECTION R318 MOISTURE CONTROL

R318.1 Vapor retarders. In all framed walls, floors and roof/ceilings that are elements of the building thermal envelope, a Class II vapor retarder shall be installed on the warm-in-winter side of the insulation.

Exceptions:

- 1. In construction where moisture or freezing will not damage the materials.
- 2. Where the framed cavity or space is ventilated to allow moisture to escape.
- 3. Class III vapor retarders shall be permitted for framed walls where either of the following conditions apply:
 - 3.1. Vented cladding is installed over wood structural panels.
 - 3.2. Continuous air impermeable insulation is applied on exterior above-grade wall surfaces.

R318.2 Moisture content. Prior to the installation of interior finishes, the building official shall be notified in writing by the general contractor that all moisture-sensitive wood framing members used in construction have a moisture content of not more than 19 percent of the weight of dry wood framing members.

This project utilized the following vapor barrier/retarder method on the walls:

- Paper Faced Insulation
- Unfaced insulation with visqueen (polyethylene plastic) applied
- A vapor block paint/ primer will be applied to the walls

Signature _____
Date