
		QTY.	SIZE	DESCRIPTION	LOCK	REMARKS		
DOORS	1	1	6 ⁰ 6 ⁸	INSULATED GALV. STEEL w/ WELDED STEEL JAMB & WEATHERSTRIPPING DEFAULT .60 U-FACTOR	SCHLAGE CYLINDER	SS BBRG NRP HINGES TEXTURED PAINT FINISH LCN1461 CLOSER VON DUPRIN 2227L PANIC DEVICE VERTICAL ROD 24" × 30" INSULATED LITE		
	2	2	3 ⁰ 6 ⁸	INSULATED GALV. STEEL w/ WELDED STEEL JAMB & WEATHERSTRIPPING DEFAULT .60 U-FACTOR	ND53PD KEYED	SS BBRG NRP HINGES TEXTURED PAINT FINISH LCN1461 CLOSER		
	3	3	3 ⁰ 6 ⁸	SOLIDCORE VINYLWRAP w/ WOOD JAMB	LC2681 Keyed	STANDARD HINGES VW OAK FINISH		
	4	2	3 ⁰ 6 ⁸	SOLIDCORE VINYLWRAP w/ WOOD JAMB	LC2675 PASSAGE	STANDARD HINGES VW OAK FINISH		
	5	2	3 ⁰ 6 ⁸	SOLIDCORE VINYLWRAP w/ WOOD JAMB	LC2676 PRIVACY	STANDARD HINGES VW OAK FINISH		
WINDOWS	$\langle 1 \rangle$			ORS TO BE 1¾" THICK LL BUMPERS FOR ALL INTERIOR DOORS ATRIUM- HORIZONTAL SLIDER, DUAL GLAZE, NFRC .350 U-FACTOR - S.H.G.C.	LOW 'E', WHITE = .38	VINYL FINISH, ARGON GAS		
	$\langle 2 \rangle$	2	24 x 48	ATRIUM- FIXED, DUAL GLAZE, LOW 'E', WHIT NFRC .350 U-FACTOR - S.H.G.C.	= .38 E VINYL FINISH,			
	$\langle 3 \rangle$	2	48 x 24	ATRIUM- HORIZONTAL SLIDER, DUAL GLAZE, NFRC .350 U-FACTOR - S.H.G.C.	LOW 'E', WHITE	VINYL FINISH, ARGON GAS		
		NOTE	: INSTALL	GALV. FLASHING UNDER SIDING AND OVER TO	OP FLANGE OF V	/INDOWS, UNDER TRIM		
2-12 PRELIMINA	RY REVIEW			AJB				_
							1	F
		EVISION		BY DATE	REVISI	•	BY	
TE								



 COPYRIGHT 2012, BLAZER INDUSTRIES, INC.

 THIS MATERIAL IS THE EXCLUSIVE PROPERTY


 OF BLAZER INDUSTRIES, INC. AND SHALL

 NOT BE REPRODUCED, USED, OR DISCLOSED

 TO OTHERS EXCEPT AS AUTHORIZED BY THE

 WRITTEN PERMISSION OF BLAZER INDUSTRIES.

OFFICE for:		Approved for Const:		Job No:	17610
Port of Siuslaw		File Copy:			
M Space Holdings	Florence, OR	Drawn By: Issue Date:	AJB 1-27-12		'




2-2-12	PRELIMINARY REVIEW	AJB				
DATE	REVISION	BY	DATE	REVISION	BY	DATE


FASTENING	SCHEDULE		MATERIAL LIST
WALLS:PLATE-TO-STUDMIN. OF 2- 0.131 x 3" NAILSVW SHEETROCKSENCO P15 STAPLES & GLUESHEETROCK-TO-STUD13 ga. x 1 5/8" SHEETROCK SCREWS AT 16" oc EDGE AND CONSTRUCTION ADHESIVE IN FIELD.PANELING-TO-STUD.030 THICK x 3/4" STAPLES @ 6" EDGE, 12" IN FIELD (SENCO K-11)	FLOOR: 2 x 8 FLOOR JOIST-TO-RIM 2 x 10 FLOOR JOIST-TO-RIM CLASS "A" BOTTOM BOARD-TO-JOIST FLOOR DECKING-TO-2x JOIST	MIN. OF 4- 0.131 x 3" NAILS (SENCO KC27 OR EQUAL) MIN. OF 5- 0.131 x 3" NAILS (SENCO KC27 OR EQUAL) 16 ga. x 3/8" WIDE CROWN @ 12" MAX. EDGES ONLY 0.113" x 2 3/8" RING SHANK @ 6" EDGE, 12" IN FIELD. (SENCO GE-24). USE CONSTRUCTION ADHESIVE (AFG01) ON JOISTS	ROOF: ROOFINGPABCO PREMIER (260 LB) ARCHITECTURAL SHINGLE OVER 2 LAYERS NON-PERF 15# FELT APPLIED SHINGLE FASHION -HIGH WIND APPLICATION- NOTE: MOP TAR UNDER SHINGLES FOR 2'-0" FROM EA. EAVE TOWARD RIDGE SHEATHING7/16" A.P.A. RATED (24/16)
BOTTOM PLATE-TO-FLOOR0.131 x 3" NAILS @ 8" oc. (SENCO KC27 OR EQUAL)SHEATHING-TO-STUD @ SIDEWALL16 ga. x 1 3/4" STAPLES @ 6" EDGE, 12" IN FIELD (SENCO N19)SHEATHING-TO-STUD @ ENDWALLSEE ENDWALL FASTENING NOTES ON ELEVATIONS.DURATEMP SIDING-TO-STUD @ SIDEWALL0.099" x 2 1/4" GALV BOX NAILS @ 6" EDGE, 12" IN FIELD (EXCEPT USE 4" oc @ TOP & BOTTOM)DURATEMP SIDING-TO-STUD @ ENDWALLSEE ENDWALL FASTENING NOTES ON ELEVATIONS.DURATEMP SIDING-TO-STUD @ ENDWALLSEE ENDWALL FASTENING NOTES ON ELEVATIONS.DURATEMP SIDING-TO-STUD @ ENDWALLSEE ENDWALL FASTENING NOTES ON ELEVATIONS.THREE STUD CORNER CONNECTION0.131 x 3" NAILS @ 12" (SENCO KC27 OR EQUAL)	ROOE: RIM-TO-RAFTERS FURRING-TO-RAFTERS ROOF RIM-TO-TOP PLATE LEDGER-TO-RIM LEDGER-TO-RIDGEBEAM	MIN. OF 5- 0.131 x 3" NAILS (SENCO KC27 OR EQUAL) (2- TOP RIM TO RAFTER, 3- MICRO RIM TO RAFTER) MIN. 4- M20 2 x 3 (MIN.) PLATES EACH SIDE 0.131 x 3" NAILS @ 8" oc. (SENCO KC27 OR EQUAL) 0.131 x 3" NAILS @ 3" oc & 3 @ BUTT JOINTS (SENCO KC27 OR EQUAL) 0.131 x 3" NAILS @ 3" oc & 3 @ BUTT JOINTS (SENCO KC27 OR EQUAL)	FRAMING
MARRIAGE LINE CONNECTION: NOTE: ALL MARRIAGE LINES (DEFINED AS THE SPACE BETWEEN ADJOINING MODULES) MUST BE INSULATED AT THE ROOF, FLOOR AND WALLS ON SITE. RIDGEBEAMS 1/2" BOLTS w/ 1 1/2" DIA. WASHERS @ 4'- 0" oc AND 8" FROM EACH END (MINIMUM 2" EDGE DISTANCE) RIM JOISTS 1/2" BOLTS w/ 1 1/2" DIA. WASHERS @ 5'- 4" oc AND 8" FROM EACH END (MINIMUM 2" EDGE DISTANCE)	PEAK TRUSS-TO-RIDGEBEAM RAFTER-TO-RIDGEBEAM RAFTER-TO-GLULLAM 2 x 4 NAILER-TO-RAFTER SHEATHING-TO-ROOF MEMBERS NC	 4- 0.131 x 3" NAILS (SENCO KC27 OR EQUAL) 3- 0.131 x 3" GALV. BOX NAILS (SENCO KC27 OR EQUAL) 3- 12d NAILS OR EQUAL TOE-NAILED 3- 0.131 x 3" NAILS (SENCO KC27 OR EQUAL) 16 ga. x 1 3/4" STAPLES @ 6" EDGE, 12" IN FIELD (SENCO N-19) DTE: SHEATHING TO BE INSTALLED PERPENDICULAR TO RAFTERS. OFFSET SHEATHING 4 ft. BLOCK EDGES OF ANY PIECES LESS THAN 24". 	CEILING
NGERS AT ALL RATTERS LEMAL DIFLUINGS MI H X 15' MALS INTO M ROO' RM M ROO' RM			MOIST-STOP. WRAP BUILDING W/ TYPAR HOUSEWRAP. INSTALL 'Z' FLASHING AT BOTTOM OF SIDING AND AT GABLE END SIDING BREAK FASCIA


7 A-4

PRELIMINARY NOT FOR CONSTRUCTION

OFFICE for:
Port of Siuslaw
M|Space HoldingsApproved for Const:Job No:17610Image: Space HoldingsFlorence, ORImage: Space HoldingsAJB
Issue Date:1-27-12







WALL "2" ELEVATION


2-2-12	PRELIMINARY REVIEW	AJB							COPYRIGHT 2012, BLAZER INDUSTRIES, INC.	• D /	MODULAR	OFFICE for:	Арр	roved for Const:	Job No: 17610
									OF BLAZER INDUSTRIES, INC. AND SHALL NOT BE REPRODUCED. USED. OR DISCLOSED	" Mazer	28 x 64	Port of Siuslaw	File	Сору:	
DATE	REVISION	BY DAT	TE	REVISION	BY	DATE	REVISION	BY	TO OTHERS EXCEPT AS AUTHORIZED BY THE WRITTEN PERMISSION OF BLAZER INDUSTRIES.	INDUSTRIES, INC. www.blazerind.com P.O. BOX 489 ■ Aumsville, OR 97325-0489	OR. GOLD	M Space Holdings	Florence, OR Issu	vn By: AJE e Date: 1-27-12	HJ








A







PRELIMINARY NOT FOR CONSTRUCTION